

A260SP Stainless Steel Hand Dryer

AUTOMATIC – No. 15304



FEATURES

Fully automatic infra-red operation. Heavy duty welded stainless steel enclosure. Fast drying cycle with high velocity blower. Long life motor and carbon brushes. Easy to clean surfaces. Hygiene and safety approved.

SPECIFICATIONS

Construction and finish: Enclosure, 1.2 mm, polished 304 satin stainless steel, ABS base, Class 1-requires grounding, all plastics flame retardant to UL94 VO. Gross weight 3.7kgs. Shipping weight 4kgs. Colour: stainless steel with grey trim. Electrical rating 220-240 V- 50-60Hz, 2.40 kW, 10AMP. Noise level 74 dB. Air volume 5.4 M3/min. Air velocity 175 km/hr.

PLANNING

Generally, one hand dryer is recommended for every two hand basins. For heavy use in large washrooms, use two hand dryers for every three basins. Automatic model A260SP must be mounted with clear space underneath the dryer to prevent interference to the infra-red control which operates in that zone. Install hand dryers adjacent to wash basins, out of the way of projecting storage cabinets or other objects to optimise access and movement around the dryer. In congested areas, site dryers to ensure good traffic flow between wash basins and dryers. If more than one is used, dryers should be placed at least 500mm to 600mm apart.

ELECTRICAL SAFETY APPROVALS

AS3304, AS3300, NZ6362, NZ6300, IEC335-2-23:1996, IEC 335-1:1991 incl Amend 1, EN55014, EN50082-1, EN60555-2/3, International CB Text Certificate No. AU0182, Certificate of suitability No. CS/781/Q

ELECTRICAL CONNECTION & ADDITIONAL NOTES

Installation and servicing should be carried out by a qualified person. Fixed wiring is recommended for all installations. Wiring should emerge from the wall at the position marked fixed wiring & supply cord entry. All wiring, related switches and circuit protection must be installed in accordance with local electrical wiring regulations and codes. When dryers are provided with a supply cord and plug, the plug must be located in an accessible position. This unit must be earthed. Always ensure the grounding/earth wire is connected to the cover terminal when refitting the cover.

RECOMMENDED MOUNTING HEIGHTS

From the floor to the bottom of the dryer:
Men's washrooms - 1200mm. Women's washrooms - 1150mm.
Children's washrooms ages up to 10 - 860mm. Children's washrooms ages up to 16 - 1120mm.
Disabled person's washrooms - 1015mm.


TOTAL SATISFACTION WARRANTY

Full Factory Warranty – 2 years
Electronic Control Only Warranty – 10 years

DISABLED PERSON COMPLIANT

EMC COMPLIANT Z184

AN ISO 9001 CERTIFIED COMPANY



A260

